



## JINAN ZHONGTIAN INTERNATIONAL TRADING CO., LTD

Φ Φ  
Φ Φ

<b>Product configuration</b>	<b>Electric control system</b>	Shanghai lezhan		
	<b>Cylinder</b>	Chuzhou Kangda		
	<b>Explosion proof valve</b>	Italian les		
	<b>seal ring</b>	Japan NOK		
	<b>Drive wheel</b>	Gilforth		
	<b>Power battery</b>	Lishi or Chaowei		
	<b>chassis</b>	Q345 manganese steel		
	<b>surface treatment</b>	Electrostatic spraying		
<b>Technical parameters</b>	<b>Platform load</b>	240KG	<b>wheelbase</b>	1.0M
	<b>Maximum workers</b>	1	<b>up and down speed</b>	34-25SEC
	<b>platform height</b>	4.00M	<b>Lifting motor</b>	24V0.8KW
	<b>Work height</b>	6.00M	<b>Battery</b>	2*12V*100AH
	<b>Self-Length</b>	1.32M	<b>tyre</b>	0.23*0.08M
	<b>Self-Width</b>	0.76M	<b>Max Climb Capability</b>	25%
	<b>Self-Height</b>	1.83M	<b>Max working angle</b>	1.5-2
	<b>Platform size</b>	1.15M*0.6M*1.1M	<b>Charger</b>	24V12A
	<b>Extension size</b>	0.55M	<b>Machine weight</b>	660KG
	<b>Extended load</b>	100KG	<b>Min ground clearance</b>	19mm
<b>Product selling points</b>	<b>Walking lifting</b>	walk and lift can be completed through the operation of the upper control handl		
	<b>Extension platform</b>	It can cross obstacles and quickly spread to the operation point.		
	<b>Turning radius</b>	The minimum turning radius and compact design facilitate operation in a narrow space		
	<b>Emergency descent</b>	The equipment can be lowered manually in case of power failure or emergency		
	<b>Explosion oil cylinder</b>	Once the oil pipe is broken, the explosion-proof valve will open automatically, wait		
	<b>Climbing ability</b>	25% climbing ability, able to climb the slope smoothly		
	<b>Convenient maintenance</b>	The fault code is displayed automatically, which is convenient for maintenance		
<b>Safety test</b>	<b>seal ring</b>	NOK sealing ring, no oil leakage when the equipment is parked for a long time		
	<b>mechanical strength</b>	More than ten times the test requirements		
	<b>Hydraulic bear capacity</b>	More than eight times the test requirements		
	<b>Electric appliance</b>	European EC declaration of conformity		
<b>Anti tilt test</b>	150% full load, 4 times the maximum tilt angle, 200N horizontal force, the load is on the most unfavorable side to ensure that the equipment does not tip over			

