Jinan Zhongtian International Trading Co.,ltd

Jinan Zhongtian International Trading Co.,Ltd.

Add: Y2-1320. Wanda Plaza. High-tech Zone, jinan city. shandong. china Mobile:+86 13075302088 Tel:+86 531 88890369 Email:alina@chinalifter.cn

Туре	Loading capacity	Lifting height	Working height
Articulated boom lift ZTGTZZ-16	230kg	16m	18m

Technical parameter:

	i pai ametei .		
	Items	parameter	
1	Maximum working height	18m	
2	Maximum platform height	16m	
3	Maximum operating radius	8.8m	
4	Maximum crossing height	8.3m	
5	Maximum load	230kg	
6	Driving type	Electric drive	
7	Battery capacity	2V×24/250AH	
8	Driving Motor Power	5.5kw/DC48V	
9	The lifting power	4.5kw/DC48V	
10	Work table size	1.88*0.78m	
11	Maximum external dimension (L× W × H)	7.1*2.04*2.2m	
12	Height of the contracted table from the ground	400mm	
13	wheel base	2097mm	
14	wheel track	1700mm	
15	The number of arms	3 Section (section 3 is the telescopic boom)	

16	The deflection of the big arm	≤0.5%	
17	Walking speed (traffic condition)	4km/h	
18	climbing ability	25%	
19	Drive steering mode	4x2x2	
20	minimum turning radius	Outer wheel 4.55m /inner wheel 1.85m	
21	Self-weight	7300kg	
22	The rotation Angle of the turntable	355° discontinuous	
23	Platform rotation Angle (optional function)	±80°	
24	control voltage	24v	
25	Colour	Y <mark>ello</mark> w/Blue	

Description of equipment main material selection and design

Our company produces the Articulated boom lift lift operation platform selection of hydraulic pump station is the liaoning anshan power production lift platform of special hydraulic pump station, the biggest advantage of pumping station is of small size, compact structure, easy leakage characteristics, the highest pressure can reach 30 mpa, the service life of the pump can start not less than 500000 times in a row, but also reduce the noise of the hydraulic station to minimum db value (from 1 m in not more than 55 decibels), lifting ability strong, safe and reliable operation is simple, we choose the hydraulic oil cylinder is the domestic famous quality products, the seal and seal all imported from Germany (DE's seal company), The company is the world famous sealing ring manufacturer, can guarantee its products run 300,000 times without oil leakage and damage, the oil cylinder outlet is installed with automatic closure valve, to prevent the closure after the pipe burst suddenly, in addition, all products are equipped with emergency descent device. The series platform for crank arm type lifting operation platform, platform lifting power dc, ac, two phase or three phase power, control switch for safe voltage, table top is equipped with control system, convenient operation, flexible, safe, and guarantee the steady lifting, main body structure of the main frame is used (Shanghai iron and steel

company production of 16 mn good-quality and rectangular pipe welding), the material with high intensity,

strong bending resistance, corrosion resistance, all rotating parts are lubricated bearing and equipped with pressure oil cup, ensure smooth hydraulic lift platform lift, flexible rotation, no noise bearing capacity amounting to more than 40 kn platform under normal use, Maintenance and timely use up to 30 years, you can rest assured use. The lifting platform produced by our company has all passed the GB/T19001-2016/ISO3001:2015 quality management system certification, and is a trustworthy enterprise brand.

Notes:

1.Packing: standard import container

2.Port of loading: QINGDAO. China

3.Delivery time: 25 working days after receipt of payment

4. Warranty: 12 months after shipment

5. Payment term: Prepaid 30%TT deposit, pay the balance due before shipment.

6.Documents with shipment: installation guide, maintenance guide, operation manual, electric diagram, hydraulic diagram, quick-wear part, etc. (all in English)













Manufacturer/Holder____

2. Certificate of Compliance of Certification

Corporate Name Jinan Zhongtian

International Trading

Co., Ltd.

Address

Y2-1320, Wanda Plaza,

High-tech Zone, Jinan,

Shandong,

Country

China

Holder

As above

of Certification Mark No. 1N180720.JZIDS27

EC Type Examination of Compliance

3. Certification Mark



4. Verification to Standard

EN ISO 12100:2010, EN 280:2013+A1:2015,

EN 60204-1:2006+A1:2009+AC:2010

Related to Directive: 2006/42/EC (Machinery)

5. Product Type - Model(s)

Туре

Annex IV - Category no. 17

Model(s)

Lift Platform

Devices for the lifting of persons or of persons and goods involving a hazard of falling from a vertical height of more than three metres. ZTSJY, ZTSJYŁ, ZTTM, ZTDCQY, ZTDCQG, ZTGTJZ, ZTJCPT, ZTSJD, ZTSJG, ZTVL, ZTSL, ZTCX, ZTCP, ZTGTBZ, ZTGTZZ, ZTQB, ZTTG, ZTZLP, ZTGTJL, ZTTPF, ZTGTWY, ZT, ZTBE, ZTFM, ZTCL.

6. Technical data

Load capacity: 200 tons Strike/Height: 300m Supply: Electrical Persons: 1-20 Speed: 0,05-6 m/s

7. Remark

The product(s) satisfies the requirements of the Safety Compliance Mark of ECM, in reference to the above listed Standard(s). The above Certification Safety Mark can be affixed on the product(s) accordingly to the ECM regulation (see www.entecerma.it) about its release and its use.

Whereas the Manufacturer is responsible of the CE certification of the product(s) and not exempted to perform all the necessary activities before placing the product(s) on the market. The Manufacturer is also responsible to maintain efficient the internal production control to ensure the product(s) is in compliance with the Safety Compliance Mark.

This certificate can be checked for validity at www.entecerma.it

8. Release date

Place: Valsamoggia (BO) - ITALY Date: 22/08/2018 Expiry date 19/07/2023 ECM - Ente Certificazione Macchine Srl

Amanda Payne (Deputy Manager)

Ente Certificazione Macchine Srl